



### Specifications

CAMERA	
<b>Sensor</b>	1/3", 4.0 megapixel, progressive scan, CMOS
<b>Lens</b>	3.6mm fixed lens
<b>Shutter</b>	Auto/Manual, 1/6~1/100000 s
<b>Minimum Illumination</b>	0.05Lux/F1.2 (Color), 0.01Lux/F1.2(B/W)
<b>Day/Night</b>	Auto (ICR) / Color / B/W
<b>Digital noise reduction</b>	2D/3D DNR
<b>IR Range</b>	Up to 20m
<b>Defog</b>	Digital Defog
<b>WDR</b>	120db
VIDEO	
<b>Video Compression</b>	Ultra265, H.265, H.264, MJPEG
<b>H.264 code profile</b>	Baseline profile, Main Profile, High Profile
<b>Frame Rate</b>	Main Stream 4.0MP@15fps / 3.0MP@30fps / 1080P (2.0MP)@30fps Sub Stream 704x576 (1~25/30fps), 640x480 (1~25/30fps), 640x352 (1~25/30fps), 320x240 (1~25/30fps)
<b>HLC</b>	Supported
<b>BLC</b>	Supported
<b>OSD</b>	Up to 4 OSDs
<b>Privacy Mask</b>	Up to 8 areas
<b>ROI</b>	Up to 2 areas
<b>Motion Detection</b>	Up to 4 areas
NETWORK	
<b>Protocols</b>	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
<b>Compatible Integration</b>	ONVIF
INTERFACE	
<b>Network</b>	1 RJ45 10M/100M Base-TX Ethernet
GENERAL	
<b>Power</b>	DC12V 300mA/ POE (802.3af)
<b>Protocols</b>	Power consumption: Max 7.8W
<b>Dimensions (W x H x D)</b>	198 x 67 x 143 (mm)

### Features

#### Optics:

- Day/night functionality
- Smart IR, up to 20m IR distance
- 2D/3D DNR (Digital Noise Reduction)
- IR anti-reflection window to increase the infrared transmittance

#### Compression:

- Ultra265, H.265, H.264, MJPEG
- MJPEG Dual streams

#### Network:

- ONVIF Conformance

#### Structure:

- IK10 vandal resistant
- Wide voltage range of  $\pm 25\%$
- IP67

# 2MCIP-4MIR20-E

4MP Vandal-resistant No Grip Network IR Fixed Corner Camera

<b>Weight</b>	1.14 lbs
<b>Working Environment</b>	14F to 122F RH 90% Max
<b>Ingress Protection</b>	IP67
<b>Vandal Resistant</b>	IK10
<b>Reset Button</b>	Supported

## Dimensions

