



Features

- Certifications: ATEX, IECEx
- Application: Suitable for Gas Zone 1 & 2, Dust Zone 21 & 22
- Explosion Protection: Ex db IIC T6 Gb / Ex tb IIIC T80°C Db
- Material: Stainless Steel 304/316L
- Enclosure Protection: IP66, IP68 (2m for 2h), IP69
- Power Input Options: PoE, DC12V (standard), AC100-240V, AC24V, DC24V

Accessories

Wall bracket with adaptor



Max Loading: 20kg
Gross Weight: 2.5kg



Corner bracket & Pole mount adaptor



Max Loading: 100 kg
Gross Weight: 6 kg
Net Weight: 5.4 kg
Overall Dimension: 326 x 184 x 180 mm



Gross Weight: 7.1 kg
Net Weight: 6.6 kg
Overall Dimension: 280 x 182 x 202 mm

Ceiling Bracket & Mount Adaptor



Max Loading: 30 kg
Gross Weight: 3 kg
Net Weight: 2.5 kg
Flexible Joint: Yes

Gross Weight: 0.8 kg
Net Weight: 0.6 kg



Specifications

GENERAL SPECIFICATIONS

Rated Voltage	AC100-240V
Power Consumption	Max 9.5 W
Certificate	ATEX, IECEx certified
ATEX marking	II 2 G Ex db II C T6 Gb II 2 D Ex tb IIIC T80°C Db
IECEx marking	Ex db IIC T6 Gb/Ex tb IIIC T80°C Db
Operating Humidity	≤ 95%
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Protection Level	IP66 IP68 (2m 2h) IP69
Dimensions (L x W x H)	270.50 x 166.00 x 160.00 mm
Gross Weight	6.5 kg / 14.33 lbs
Net Weight	5.6 kg (12.34 lb)
Cable thread hole	1set M25*1.5 (standard), M27*1.25
Material	Stainless steel 304/316L

Dimensions

