



Features

- Explosion Proof Thermographic Thermal & Optical Bi-spectrum Network Camera housing
- Certifications: ATEX, IECEx
- Application: Suitable for Gas Zone 1 & 2, Dust Zone 21 & 22
- Material: Stainless Steel 304/316L
- Enclosure Protection: IP66, IP68 (2m for 2h), IP69
- Power Input Options: PoE, DC12V (standard), AC100-240V, AC24V, DC24V

Specifications

GENERAL SPECIFICATIONS	
Rated Voltage	AC100-240V
Power	≤36W(Without heat and fan) ; ≤25W(PoE)
Certificate	ATEX : DNV 22 ATEX 54162X, IECEx: IECEx DNV 22.0101
Certificate mark	II 2 G Ex db II C T6 Gb II 2 D Ex tb IIIC T80°C Db
Air pressure	80KPa~110KPa
Ambient temperature	- 40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	≤ 95%
Storage Temperature	- 20°C to 150°C (-4°F to 302°F)
Protection Level	IP66 IP68 (2m 2h) IP69
Dimensions (L x W x H)	328.8 × 156 × 169.4 mm
Net Weight	6.3 kg / 14.9 lbs
Material	Stainless steel 304/316L
Accessories	Wall mount, Pole mount and corner mount

Dimensions

